

# Turbo-Flo™ Z Series

## UTILITY PUMPS



流动的创新

## WILDEN®

Born from the grass roots era of industrial manufacturing, and then improving upon the design over the past 50+ years, Wilden's Turbo-Flo™ Z Air Distribution System (ADS) is a culmination of years and years of experience in some of the most demanding and difficult pump applications the world has to offer. As the successor to the Turbo-Flo™ ADS that originated the air-operated double-diaphragm industry back in 1955, Turbo-Flo™ Z offers the reliability and performance that is expected from a world leading pump manufacturer. Along with being reliable, this air distribution system provides lube-free operation, easy to maintain, and is economically conscious as well.

With experience that speaks for itself, Wilden knows how to maximize your yield, increase your up-time and reduce costs associated with your pumping needs. Tap into our wealth of experience and knowledge; together with our full service local distributors, we have qualified individuals to specify, install, maintain, troubleshoot, or repair your equipment. To purchase a new Wilden Original™ Series pump fitted with the Turbo-Flo™ Z air distribution system contact your authorized Wilden distributor today.

**TURBOFLO™**  
PROGRESSIVE PUMP TECHNOLOGY **Z**

### FEATURES AND BENEFITS

- Lube-free operation
- Simplicity of design
- Ease of maintenance & operation
- Flow rates to 909 lpm (240 gpm)
- On/Off reliability

[WWW.WILDENPUMP.COM](http://WWW.WILDENPUMP.COM)



## TOUGH APPLICATIONS ARE NOT SO TOUGH WITH TURBO-FLO™ Z

Wilden's Turbo-Flo™ Z pumps are designed and manufactured for both general and specialized applications found in a wide variety of industries ranging from paints and inks to water and wastewater and many, many more. Another advantage of Wilden's Turbo-Flo™ Z pump is simplicity of design; engineered with the lowest number of moving parts in the industry this pump assures that your maintenance programs result in lower direct maintenance expenses and reduced downtime.

- Solvents
- Acids
- Caustics
- Hazardous Liquids
- High Viscosity
- Low Viscosity

## PUMP SELECTION

Product Series	Wetted Path	Construction	Size					Certifications
			13mm 1/2"	25mm 1"	38mm 1-1/2"	51mm 2"	76mm 3"	
<b>Turbo - Flo™ Z</b>  Max Flow Rates: 54.9 lpm - 909 lpm (15.8 gpm - 240 gpm)	Aluminium	Clamped						CE Ex
	Ductile Iron	Clamped						CE Ex
	Stainless Steel	Clamped						CE Ex
	Polypropylene	Clamped						CE

流 动 的 创 新



欢迎关注官方微信

PSG

No.2 Haitai Huaker Er Road, Huayuan Industrial Park,  
Tianjin, 300384 China

P: +86(22)2380 5000 • F: +86(22)2791 1577

psg-china@psgdover.com

cn.psgdover.com

Distributed By: